



Proudly  
made in Italy



# VetAssure B18 & B23

B-class 18 and 23-liter autoclaves



## Antimicrobial Treatment

BioCote antimicrobial coating inhibits the growth of microbes, such as bacteria and fungi, on the autoclave's side and top panels, ensuring a hygienic environment.



## Standard Water Pump

Thanks to the built-in frontal water pump, you can keep the tank on the ground. Simply press a button, and the autoclave will fill itself up. The drainage, on the other hand, can be either manual or automatic.



## Built-In Reverse Osmosis

Include the optional ROSI® to effortlessly connect your unit to tap water. This configuration offers an impressive average of 1,300 cycles of operation before maintenance is required.



## Free Integrated Printer

Simply document and monitor your sterilization processes to ensure compliance and streamline operations.



## Paperless

The optional data logger conveniently saves sterilization records onto a USB drive. Coupled with our proprietary software, you can easily access and read the records on your PC.



## Field Deepest Chamber

Among autoclaves with the same capacity, our 23 L unit proudly features the deepest chamber, measuring an impressive 530 mm.

Sterilization Cycles	VetAssure B18	VetAssure B23
Helix Test (min, steriliz. time: 3.5 min)	25	35
134°C Bowie-Dick Test (min, steriliz. time: 3.5 min)	25	35
Vacuum Test (min)	15	15
134°C Hollow Wrapped (min, steriliz. time: 5 min)	32	42
121°C Hollow Wrapped (min, steriliz. time: 18 min)	40	50
134°C Prion (min, steriliz. time: 20 min)	39	49
134°C Porous (min, steriliz. time: 5 min)	32	42
121°C Porous (min, steriliz. time: 18 min)	42	52
134°C Rapid (min, steriliz. time: 5 min)	31	41

Note: Values include pre-heating and drying; times vary with load and power supply.

Technical Specifications	VetAssure B18	VetAssure B23
Autoclave Class	B	B
Chamber Volume	18 L	23 L
Chamber Dimensions (Ø x d)	236 x 381.5 mm	236 x 530 mm
Chamber Max. Fitting Cuboid Dimensions (w x d x h)	166 x 380 x 166 mm	166 x 529 x 166 mm
Max. Load Quantity	2.5 kg wrap. instr. 4 kg unwrap. instr. 1 kg textiles	3.5 kg wrap. instr. 4.5 kg unwrap. instr. 1.5 kg textiles
Device Dimensions (w x d x h)	505 x 615 x 400 mm	505 x 690 x 400 mm
Weight	52 kg	58 kg
Power Supply	220 – 240 V 50 – 60 Hz	220 – 240 V 50 – 60 Hz
Power Consumption	2,400 W	2,400 W

Note: The autoclave is intended for use in veterinary medicine. It is not a medical device according to Reg. (EU) 2017/745 (MDR).